

### SPRAY F-29

QUICK DRYING ZINC PHOSPAHTE PRIMER

Edition: 020 2017/12

Cod: 3002907040097.00000.020

#### APPLICATION

Quick drying anti-oxydant synthetic primer, high filling power, smooth and silky finish, hard, flexible, good adhesion and recoatable. Suitable for touch-up in boilermaking sector, industrial vehicle, agricultural machinery, metallic structure, etc  
VOC content lower than 840 g/l (2004/42/CE) IIB (E).

#### SURFACE PREPARATION

The surface (steel and iron) must be rust free, degreased and dry.  
On old paints, sand previously with 360-400.  
Recoatable with 1k y 2k topcoats.

#### APPLICATION INSTRUCTIONS

Shake the can during 2-3 minutes before using Spray F-29.  
Apply in 2-3 layers, leaving 5-10 min. in between layers.  
Having used the spray, turn it upside down and press in order to clear the nozzle.



Painting range  
20-30 cm



30-40 my



5-10 min.



Dry 30 min.

#### FEATURES OF DRY FILM

Colour	Grey 7040
Gloss 60°-60°	Matt <5%
Second layer	6-8 h

#### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.  
CAUTION: Do not expose the can to temperature over 50°C.  
Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.